

## Dosing Pump ANALOG



Model can vary from picture

### General information

- Adjustable stroke with potentiometer
- Easy and flexible installation and usage by the vertical mount design
- High resistance to corrosive chemicals with PP Pump Head and entire IP65 body
- Electronic circuit controlled electromagnet and long lasting Teflon (PTFE) diaphragm
- Lesser maintenance with ceramic ball design
- Liquid level sensor, suction and injection parts included
- Pump Head: PP / Pump Body: PP
- Suction and Injection Set: PP Zirconium Ball, Viton-EPDM\* O-Ring
- Pump Head Set: PP, Zirconium Ball, Viton-EPDM\* O-Ring
- Diaphragm: PTFE / Glands: PP / O-Rings: Viton-EPDM\*
- Suction Pipe: PVC / Injection Pipe: PE / Ventilating Pipe: PVC

### Technical Specification

ANALOG	max./lit lit/h	max./p Bar	Stroke/ min.	Stroke/ ml	Power Volt	Watt	Analog	Digital	Level Control	Water Meter Input	4-20/mA Analog Input	10% Adjustment	Alarm Output
5L/5B	5	5	180	0,463	230V/50Hz	25	✓	✗	✗	✗	✗	✗	✗
2L/10B	2	10	180	0,185	230V/50Hz	25	✓	✗	✗	✗	✗	✗	✗
0,5L/5B	0,5	5	180	0,046	230V/50Hz	25	✓	✗	✗	✗	✗	✗	✗

### Order Code

Article No.	Model	L/h	Max.Counter Pressure/Bar	Packing Sizes/cm W-L-H	Packed Weight/kg	Unit Price (€)
302105005101000	MN-A 5L/5B V220FAT	5	5	21 x 24 x 18	2.45	
302102010101000	MN-A 2L/10B V220FAT	2	10			
302100505101000	MN-A 0,5L/5B V220FAT	0,5	5			

Please notify:  
\*May vary by model